

Claims

1. Illumination system (1) having a control unit (2)
and at least one de-central lamp operating device
5 (12, 22) for operating one or more associated lamps
(LA),
wherein the lamp operating device (12, 22) can
be operated in different operational modes and,
wherein the central control unit (2) and the
10 lamp operating device (12, 22) are so configured
that the selection and setting of an operational
mode for the lamp operating device (12, 22) can be
carried out from or via the central control unit
(2).
- 15
2. Illumination system according to claim 1,
characterized in that,
at least one of the selectable operational modes of
the lamp operating device (12, 22) makes possible a
20 dimming of the associated lamp (LA) or lamps.
3. Illumination system according to claim 1 or 2,
characterized in that,
the selection and setting of an operational mode for
25 the lamp operating device (12, 22) is effected
through the transmission of a corresponding control
command from the central control unit (2).
4. Illumination system according to claim 3,
30 characterized in that,
this has a bus line system (3, 10, 20) via which the
central control unit (2) is connected with the lamp

operating device (12, 22) and which is provided for the transmission of the control commands.

5. Illumination system according to any of claims 1 to 4,
characterized in that,
the lamp operating device (12, 22) has a memory for storing the information as to which operational modes are available in what manner for operation of the lamp (LA).

6. Illumination system according to any of claims 1 to 5,
characterized in that,
the lamp operating device (12, 22) operates the lamp (LA) associated therewith corresponding to a base function, in the case that no operational mode has been selected.

7. Illumination system according to claim 6,
characterized in that,
within the scope of the base function, the lamp operating device (12, 22) switches on and switches off the lamp (LA) associated therewith.

8. Illumination system according to any preceding claim,
characterized in that,
the brightness level of the lamp (LA) in the switched-on condition, or the maximum brightness level settable by means of the lamp operating device (12, 22), is alterable by means of the central control unit (2).

9. Illumination system according to claim 8,
characterized in that,
the control unit (1) increases the switched-on
5 brightness level, or the maximum-brightness level of
the lamp (LA), with increasing operating time.
10. Illumination system according to claim 9,
characterized in that,
10 the degree of increase of the switched-on brightness
level, or the maximum brightness level, is dependent
upon the lamp type and/or luminaire type.
11. Illumination system according to claim 10,
15 characterized in that,
by means of the increase of the switched-on
brightness level, or the maximum brightness level,
an aging of the lamp (LA) and/or a dirtying of the
luminaire is compensated.
- 20
12. Lamp operating device (12, 22) for operating an
associated lamp (LA), which is operable in different
operational modes,
characterized in that,
25 the selection and setting of an operational mode for
the lamp operating device (12, 22) can be determined
externally.
13. Lamp operating device (12, 22) for operating an
30 associated lamp (LA),
characterized in that,
the brightness level of the lamp (LA) in the
switched-on condition, or the maximum brightness

level settable by means of the lamp operating device (12, 22), can be externally set.

14. Method for operating a lamp (LA) by means of a
5 lamp operating device (12, 22),
wherein the lamp operating device (12, 22) is
operable in different operational modes,
characterized in that,
the selection and setting of an operational mode for
10 the lamp operating device (12, 22) is effected
externally.

15. Method according to claim 14,
characterized in that,
15 the selection and setting of an operational mode for
the lamp operating device (12, 22) is effected by
means of the transmission of an external control
command.

20 16. Method according to claim 14 or 15,
characterized in that,
at least one of the selectable operational modes of
the lamp operating device (12, 22) makes possible a
dimming of the associated lamp (LA) or lamps.

25 17. Method according to claim 15 or 16,
characterized in that,
the lamp operating device (12, 22) operates the lamp
(LA) associated therewith in accordance with a base
30 function, in the case that no operational mode has
been selected.

18. Method according to claim 17,

characterized in that,
the lamp operating device (12, 22) switches on and
switches off the associated lamp (LA), within the
scope of the base function.

5

19. Method according to any of claims 14 to 18,
characterized in that,
the brightness level of the lamp (LA) in switched-on
condition, or the maximum brightness level which can
10 be set by means of the lamp operating device (12,
22), can be altered.

15

20. Method according to claim 19,
characterized in that,
the switched-on brightness level, or the maximum
brightness level of the lamp (LA), is increased with
increasing operational time.

20

21. Method according to claim 20,
characterized in that,
the degree of increase of the switched-on brightness
level or of the maximum brightness level is
dependent upon the lamp type and/or the luminaire
type.

25

30

22. Method according to claim 21,
characterized in that,
through the increase of the switched-on brightness
level or of the maximum brightness level an aging of
the lamp (LA) and/or a dirtying of the luminaire is
compensated.

23. Method of operating a lamp (LA) by means of a lamp operating device (12, 22), characterized in that, the brightness level of the lamp (LA) in the switched-on condition, or the maximum brightness level settable by means of the lamp operating device (12, 22), is alterable.
24. Method according to claim 23, characterized in that, the switched-on brightness level or the maximum brightness level of the lamp (LA) is increased with increasing operational time.
25. Method according to claim 24, characterized in that, the degree of increase of the switched-on brightness level or of the maximum brightness level is dependent upon the lamp type and/or luminaire type.
26. Method according to claim 25, characterized in that, by means of the increase of the switched-on brightness level or of the maximum brightness level an aging of the lamp (LA) and/or a dirtying of the luminaire is compensated.